



# EXFIL<sup>®</sup> LTP

PERFORMANCE STANDARD

BS EN 1385:2012 (Whitewater)



Featuring EXFIL<sup>®</sup> Rail 2.0



Featuring EXFIL<sup>®</sup> Rail 3.0

## SIZING

### SIZE 1

### SIZE 2

Head Circumference (cm)  
Head Circumference (in)  
Hat Size (USA)

55–60  
21.5–23.5  
6 7/8–7 1/2

up to 63  
up to 24.75  
up to 7 7/8

## COLORS

- Black (FED-STD-595C #37031)
- Coyote Brown (FED-STD-595C #20150)

## WEIGHT

Complete System: 1.59 lbs (0.72 kg)

## ENVIRONMENTAL CONDITIONS / MIL-STD-810G METHODS

501.5P1 High Temperature | 502.5P1 Low Temperature  
507.5 Humidity | 509.5 Salt Fog | 510.5P11 Blowing Sand/Dust  
514.6 Loose Cargo Vibration | 500.5P1 Low Pressure (Altitude)

## SHELL ASSEMBLY

- › Integrated Wilcox® aluminum NVG shroud built to the specifications of the SOCOM SPEAR program
- › High-cut shell with unique geometry for an optimal fit
- › Meets shock absorption requirements of BS EN 1385:2012
- › EXFIL® Rail 2.0 System or EXFIL® Rail 3.0 System available for side accessory rails

### Materials

- › Shell: Lexan polycarbonate copolymer
- › VELCRO® USA: Loop 1100, military loop
- › Hardware: Stainless steel with MIL-DTL-13924D black oxide coating
- › Side Accessory Rails: Glass reinforced polycarbonate

## LINER SYSTEM

- › Three-piece Zorbium® foam impact liner with six modular comfort pads, all Berry compliant materials
- › Meets shock absorption requirements of BS EN 1385:2012

### Materials

- › Zorbium®: Proprietary polyurethane impact and comfort foam also used in the standard issue U.S. Army and Marine Corps 7-Pad System
- › Impact Liner: Proprietary water-resistant film and loop fabric covering
- › Comfort Pads: Proprietary water-resistant film and antimicrobial wicking fabric covering

#### Part Numbers

Size 1 Black Rail 2.0: 72-215  
Size 2 Black Rail 2.0: 72-225

Size 1 Coyote Brown Rail 2.0: 72-315  
Size 2 Coyote Brown Rail 2.0: 72-325

Size 1 Black Rail 3.0: 72-R3-215  
Size 2 Black Rail 3.0: 72-R3-225

Size 1 Coyote Brown Rail 3.0: 72-R3-315  
Size 2 Coyote Brown Rail 3.0: 72-R3-325

## RETENTION

- › Team Wendy® CAM FIT™ Retention with Boa® Fit System for optimized stability and fit
- › Cam Lock sliders for one-handed adjustment and secure fit

### Materials

- › Boa® Fit System with micro-adjustable dial, coated stainless steel cable and low friction guides
- › MIL-DTL-32067 leather chin cup
- › 5/8" nylon webbing
- › Acetal buckles and cams
- › 500D Cordura nape pad with Zorbium® foam
- › Antimicrobial wicking headband sleeves

## AVAILABLE ACCESSORIES

### SHOCK CORD KIT INCLUDED

#### EXFIL® LTP HELMET COVERS

Mesh and Nylon spandex cover available in Black, Coyote Brown, MultiCam®, MultiCam® Alpine, Ranger Green and Wolf Gray

#### EXFIL® OXYGEN MASK STRAP KIT

For attachment of Airborne Systems SOLR® and PHAOS, and Cobham PHANTOM O2 masks

#### EXFIL® PELTOR™ HEADSET ADAPTERS

Provides direct rail mount of all Peltor™ ComTac™ systems (quick release optional for EXFIL® Rail 2.0; required for EXFIL® Rail 3.0)

#### EXFIL® QUICK RELEASE RAIL ADAPTERS

Tool-free accessory attachment, includes two 5-slot Picatinny rails

#### EXFIL® RAIL 2.0 ACCESSORY KIT

Includes two goggle posts and two "MINI-TINNY" 2-slot Picatinny rails (MINI-TINNY not compatible with EXFIL® Rail 3.0)